

## Technical Parameters

| MODEL   | DESIGN PRESSURE (bar) | DIMENSION (in) | FLANGE |
|---------|-----------------------|----------------|--------|
| BL6     | 30/45                 | 4.685*2.165    | DN10   |
| BL12    | 30/45                 | 5.984*2.992    | DN15   |
| BL13    | 30/45                 | 3.011*7.637    | DN15   |
| BL14    | 30/45                 | 2.992*8.11     | DN20   |
| BL14D   | 10                    | 2.795*7.322    | DN20   |
| BL15A   | 10                    | 3.267*7.598    | DN20   |
| BL14W   | 30/45                 | 3.07*8.11      | DN20   |
| BL16    | 30/45                 | 3.07*8.11      | DN20   |
| BL17    | 30                    | 3.346*7.952    | DN20   |
| BL18    | 10                    | 3.582*8.267    | DN20   |
| BL20    | 30/45                 | 3.031*12.48    | DN20   |
| BL20W   | 30/45                 | 2.952*12.401   | DN20   |
| BL21    | 45                    | 2.992*12.283   | DN20   |
| BL25    | 30/45                 | 3.622*12.677   | DN25   |
| BL26    | 30/45                 | 4.291*12.204   | DN32   |
| BL26W   | 30/45                 | 4.173*12.047   | DN32   |
| BL30    | 30/45                 | 4.881*11.968   | DN32   |
| BL37AS  | 21/45                 | 4.763*13.07    | DN25   |
| BL40AS  | 21/45                 | 4.685*14.803   | DN25   |
| BL51    | 30/45                 | 4.251*20.669   | DN32   |
| BL60    | 30/45                 | 4.685*20.708   | DN32   |
| BL61AS  | 30/45                 | 4.645*20.629   | DN32   |
| BL95A   | 30/45                 | 7.362*24.251   | DN50   |
| BL95B   | 30/45                 | 7.362*24.251   | DN50   |
| BL95C   | 30/45                 | 7.362*24.251   | DN65   |
| BL95FAS | 30                    | 24.133*7.283   | DN50   |

## Technical Parameters

| MODEL   | DESIGN PRESSURE (bar) | DIMENTION (in)       | FLANGE       |
|---------|-----------------------|----------------------|--------------|
| BL120   | 30/45                 | 9.645*20.826         | <b>DN50</b>  |
| BL122   | 30/45                 | <b>9.685*20.826</b>  | <b>DN50</b>  |
| BL125   | 30                    | <b>9.763*20.866</b>  | <b>DN50</b>  |
| BL150AS | 21/30                 | <b>10.236*27.401</b> | <b>DN80</b>  |
| BL180   | 21                    | 10.078*33.307        | <b>DN65</b>  |
| BL190   | 15/21/30              | 12.086*27.48         | <b>DN80</b>  |
| BL195   | 15/21/30              | 12.047*27.322        | <b>DN80</b>  |
| BL200   | 15/21/30              | 12.598*29.133        | <b>DN100</b> |
| BL350   | 30                    | 11.968*38.622        | <b>DN100</b> |
| BL600   | 15/21                 | 17.165*55.236        | <b>DN125</b> |

## Technical Parameters

| MODEL    | DESIGN PRESSURE (bar) | DIMENSION (in)      | FALNGE |
|----------|-----------------------|---------------------|--------|
| BL100    | 30/45bar              | <b>9.763*19.527</b> | DN50   |
| BL100E   | 30/45bar              | <b>9.763*19.488</b> | DN50   |
| BL100EW  | 30/45bar              | 9.566*19.33         | DN50   |
| HBL130AS | 45bar                 | 11.535*20.944       | DN65   |
| BL210    | 30/45bar              | 12.598*29.015       | DN80   |

## Technical Parameters

| MODEL  | DESIGN PRESSURE (bar) | DIMENSION (in) |
|--------|-----------------------|----------------|
| B30    | 10                    | 18.897*7.086   |
| B60    | 10/16                 | 36.22*12.598   |
| BB100  | 10                    | 41.141*17.874  |
| BH100  | 16                    | 42.086*18.503  |
| B150   | 10/16                 | 71.456*24.015  |
| B200   | 10/16                 | 88.976*30.708  |
| B250   | 10/16                 | 114.291*36.22  |
| B350   | 10/16                 | 113.464*45.275 |
| L100   | 10/16                 | 74.33*18.897   |
| L100C  | 10                    | 69.685*18.897  |
| LB100T | 10                    | 70*19.842      |
| LD100T | 25                    | 70.511*22.44   |
| LB60   | 10                    | 49.763*12.598  |
| S60    | 10/16                 | 27.716*15.748  |
| S200   | 10/16                 | 55.314*31.496  |
| BH65   | 10                    | 37.244*14.96   |

## Technical Parameters

| MODEL | DESIGN PRESSURE (bar) | DIMENSION(in) |
|-------|-----------------------|---------------|
| BS30  | 10                    | 18.897*7.086  |
| BS60  | 10                    | 37.795*12.598 |
| BS100 | 10                    | 42.716*17.874 |
| BS150 | 10                    | 71.456*24.015 |
| BS200 | 10                    | 88.976*30.708 |
| FB30  | 10                    | 18.897*7.086  |
| FB60  | 10                    | 35.629*12.204 |
| FB100 | 10                    | 41.456*17.401 |
| FB150 | 10                    | 83.543*24.015 |